## **AWTA Product Testing**

Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106

1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400 Fax (03) 9371 2499

## **TEST REPORT**

Client: Tarkett Australia Pty Ltd

> Suite 1 Level 3 3 Columbia Court Baulkam Hills NSW 2153

**Issue Date** 

18-003918 9/08/2018

**Print Date** 

Test Number :

10/08/2018

**Sample Description** 

Clients Ref:

Width

"Starfloor Click Ultimate"

Vinyl floorcovering

Nominal Composition:

PVC

Nominal Mass per Unit Area/Density:

6.5mm

11,3kg/m2

Nominal Thickness:

AS/ISO 9239.1-2003

Reaction to Fire Tests for Floorings. Determination of the Burning Behaviour using a **Radiant Heat Source** 

Date of Sample Arrival 11/07/2018 **Date Tested** 08/08/2018

**CHF Value** 1 2 3 Mean Length 10.1 10.2 10.5 10.3 kW/m<sup>2</sup> Width 10.5 kW/m<sup>2</sup> Smoke Value 2 3 Mean Length 207 244 240 230 %.min

Blistering Yes Smouldering Yes

243

138712 29150 Page 1 of 2

Australian Wool testing Authority Ltd Copyright - All Rights Reserved



Accredited for compliance with ISO/IEC 17025 - Testing - Chemical Testing

Mechanical Testing

Performance & Approvals Testing

: Accreditation No Accreditation No

: Accreditation No 1356

983

Samples and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results

APPROVED SIGNATORY

A. JACKSON B.Sc.(Hons)

%.min

relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if amended or altered. This document, the names AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved by the Managing Director of AWTA Ltd.

## **AWTA PRODUCT TESTING**

Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106

1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400 Fax (03) 9371 2499

## **TEST REPORT**

Client: Tarkett Australia Pty Ltd

Suite 1 Level 3 3 Columbia Court Baulkam Hills NSW 2153 **Test Number** : 18-003918 **Issue Date** : 9/08/2018

**Print Date** : 10/08/2018

The test results relate to the behaviour of the test specimens of a product under the particular conditions of the test, they are not intended to be sole criterion for assessing the potential fire hazard of the product in use.

Sample was conditioned in accordance with BSEN 13238:2010 at a temperature of 23±2°C and relative humidity of 50±5% for a minimum of 48 hours prior to testing.

Each specimen was adhered to a substrate of 6mm thick fibre reinforced cement board using Roberts 656 adhesive and clamped prior to testing.

HF30 not reported as flame out time occurred before 30 minutes.

138712 29150 Page 2 of 2

Australian Wool testing Authority Ltd Copyright - All Rights Reserved



Accredited for compliance with ISO/IEC 17025 - Testing - Chemical Testing

Mechanical Testing

- Performance & Approvals Testing

: Accreditation No. : Accreditation No.

: Accreditation No.

983 985 1356



A. JACKSON B.Sc.(Hons)

Samples and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if amended or altered. This document, the names AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved by the Managing Director of AWTA Ltd.

- /

MANAGING DIRE

APPROVED SIGNATORY