



SUITE 17, 808 FOREST ROAD, PEAKHURST 2210 ABN: 73 107 291 494
P. 02 9046 3800 ACOUSTICS@DAYDESIGN.COM.AU WWW.DAYDESIGN.COM.AU

Acoustic Opinion

LVT Ultimate Flooring Systems

REPORT No
6577-1.1R

DATE ISSUED
10 September 2018

Prepared For:
Tarkett Australia Pty Ltd
3 Columbia Court
Baulkham Hills NSW 2153

Attention: Mr Reza Karani



Acoustic Opinion**Revision History**

Report	Date	Prepared	Checked	Comment
Draft	04/09/2018	Stephen Gauld	William Wang	By email, for client review
Final	10/09/2018	Stephen Gauld	William Wang	

Document R\6577-1.1r, 9 pages plus attachments

Disclaimer

The work presented in this document was carried out in accordance with the Day Design Pty Ltd Quality Management System. Day Design is certified to ISO9001.

Day Design Pty Ltd is a member company of the Association of Australian Acoustical Consultants, and the work herein reported has been performed in accordance with the terms of membership.

Day Design Pty Ltd reserves all copyright of intellectual property in any or all of Day Design's documents. No permission, license or authority is granted by Day Design to any person or organisation to use any of Day Design's documents for any purpose without written consent of Day Design.

This report has been prepared for the client identified in Section 1.0 only and cannot be relied or used by any third party. Any representation, statement, opinion or advice, expressed or implied in this report is made in good faith but on the basis that Day Design is not liable (whether by reason of negligence, lack of care or otherwise) to any person for any damage or loss whatsoever which has occurred or may occur in relation to that person taking or not taking (as the case may be) action in any respect of any representation, statement, or advice referred to above.

Recommendations made in this report are intended to resolve acoustical problems only. No claims of expertise in other areas are made and no liability is accepted in respect of design or construction for issues falling outside the specialist field of acoustical engineering including but not limited to structural, fire, thermal, architectural buildability, fit for purpose, waterproofing or other aspects of building construction. Supplementary professional advice should be sought in respect of these issues.

The information in this document should not be reproduced, presented or reviewed except in full. Prior to passing onto a third party, the Client is to fully inform the third party of the specific brief and limitations associated with the commission.



TABLE OF CONTENTS

1.0	CONSULTING BRIEF.....	4
2.0	PREDICTION OF $L'_{nT,w}$	5
3.0	MATERIALS USED FOR SOUND REDUCTION	6
3.1	Plasterboard Ceilings.....	6
3.2	Insulation.....	6
3.3	Furring Channels	6
4.0	ACOUSTIC OPINIONS.....	7
4.1	System #1	7
4.2	System #2	7
4.3	System #3	8
4.4	System #4	8
5.0	STATEMENT OF ACOUSTIC OPINION.....	9



Acoustic Opinion

1.0 CONSULTING BRIEF

Day Design Pty Ltd was engaged by Tarkett Australia Pty Ltd to provide Acoustic Opinions on the $L'_{nT,w}$ ratings for a range of their LVT Ultimate Flooring systems. The objective is to provide acoustical data useful to building designers for inclusion in Tarkett technical publications.

Scope of Work:

- Review the results of floor systems tested on site at Peakhurst.
- Model plasterboard structures using acoustic modelling software.
- Compare the $L'_{nT,w}$ predictions with test results.
- Provide Acoustic Opinions on the $L'_{nT,w}$ ratings for a range of Flooring systems.
- Prepare an Acoustical Opinion Report.



Acoustic Opinion

2.0 PREDICTION OF $L'_{nT,w}$

The impact sound insulation performance of a system is denoted by a single value descriptor, the weighted impact sound insulation $L_{n,w}$ (for laboratory tested rating) or $L'_{nT,w}$ (for field tested rating). The single value descriptor allows for easy comparisons of impact noise levels between different systems. The lower the number, the better the impact sound insulation performance.

The rating of the system is determined by comparing the measured noise levels against a set of reference values between one-third-octave band centre frequency ranges of 100 Hz to 3150 Hz, as specified in AS/NZS ISO 717.2:2004.

The Acoustic Opinions expressed in this report are based firstly on calculations made using Insul software and secondly by comparison with Impact Sound Insulation tests for similar constructions. Acoustic opinions are then provided in the light of our general acoustic experience. Factors taken into account in our calculations include: the surface mass of the plasterboard, cavity depth, Young's Modulus, the critical frequency and speed of sound in wall lining materials, the effect of air cavities and acoustic insulation between furring channels.

We are of the opinion that using Insul modelling software and making corrections based on comparison with test results, is that our prediction accuracy is in the order of ± 2 dB.

Because of the complexity of such calculations, approved laboratory test results (in accordance with Australian Standard ISO 140.7:2006 and ISO 717.2:2004) are always preferred.



Acoustic Opinion**3.0 MATERIALS USED FOR SOUND REDUCTION****3.1 Plasterboard Ceilings**

This schedule of $L'_{nT,w}$ ratings includes various ceiling constructions from plasterboard. The density of the plasterboard used in the testing and in this report is shown in Table 1 below.

Table 1 Material Densities

Product Name	Thickness (mm)	Bulk Density (kg/m ³)
Standard plasterboard	10	590
Standard plasterboard	13	808

3.2 Insulation

Acoustic insulation specified is Glasswool insulation with bulk density as follows:

Table 2 Insulation Densities

Product Name	Thickness (mm)	Bulk Density (kg/m ³)
Glasswool R1.1	35 mm	11

3.3 Furring Channels

Furring channels nominated in this report are 28 mm deep and 38 mm wide as offered by a number of manufacturers.

Deeper furring channels or other fixing structures that provide a greater cavity will provide equal or better impact sound insulation.



Acoustic Opinion**4.0 ACOUSTIC OPINIONS**

Tarkett has developed a range of floor and ceiling systems that include options for 4 different concrete slab thicknesses and 4 different ceiling configurations. Several systems were tested in a dedicated site testing facility at Day Design's office in Peakhurst, NSW. The acoustic opinions below are based on these comparable tests, Insul software as well as our own experience.

4.1 System #1

LVT Ultimate Flooring

Concrete slab, as per table below

No ceiling or insulation

System	Ceiling Lining	Concrete thickness, mm	Insulation	L' _{nT,w}
#1	No Ceiling	120	Nil	58
		150	Nil	57
		180	Nil	55
		200	Nil	54
		230	Nil	53*

* Tested on site – 24/8/2018 (ref: A007)

4.2 System #2

LVT Ultimate Flooring

Concrete slab, as per table below

Insulation R1.1 Glasswool, thickness as per table below

1 layer of 10 mm plasterboard on 28 mm furring channels

System	Ceiling Lining	Concrete thickness, mm	Insulation	L' _{nT,w}
#2	1 layer of 10 mm Plasterboard	120	35 mm	54
		150	35 mm	52
		180	35 mm	51
		200	35 mm	51
		230	35 mm	50



Acoustic Opinion**4.3 System #3**

LVT Ultimate Flooring

Concrete slab, as per table below

Insulation R1.1 Glasswool, thickness as per table below

1 layer of 13 mm plasterboard on 28 mm furring channels

System	Ceiling Lining	Concrete thickness, mm	Insulation	L' _{nT,w}
#3	1 layer of 13 mm Plasterboard	120	35 mm	53
		150	35 mm	52
		180	35 mm	50
		200	35 mm	50
		230	35 mm	49*

* Tested on site – 23/8/2018 (ref: A003)

4.4 System #4

LVT Ultimate Flooring

Concrete slab, as per table below

Insulation R1.1 Glasswool, thickness as per table below

2 layers of 13 mm plasterboard on 28 mm furring channels

System	Ceiling Lining	Concrete thickness, mm	Insulation	L' _{nT,w}
#4	2 layers of 13 mm Plasterboard	120	35 mm	53
		150	35 mm	51
		180	35 mm	50
		200	35 mm	50
		230	35 mm	49*

* Tested on site – 23/8/2018 (ref: A006)



Acoustic Opinion

5.0 STATEMENT OF ACOUSTIC OPINION

We are confident that provided the floor systems are built of the materials specified in a workmanlike manner in accordance with the manufacturer's instructions, they will provide the impact sound insulation ratings listed in the Acoustic Opinions section of this report.



Stephen Gauld, BE(Mech), MEngSc (Noise and Vibration), MIEAust, MAAS

Principal Acoustical Consultant

for and on behalf of Day Design Pty Ltd

AAAC MEMBERSHIP

Day Design Pty Ltd is a member company of the Association of Australasian Acoustical Consultants. The work herein reported has been performed in accordance with the terms of membership.

Appendices

- A007 – Test System #1, 230 mm concrete
- A003 – Test System #3, 230 mm concrete
- A006 – Test System #4, 230 mm concrete



Standardized Impact Sound Pressure Level according to ISO 140-7

Field measurements of impact sound insulation of floors

Client: Tarkett Australia Pty Ltd

Date of test: 24/08/18

Description and identification of the building construction and test arrangement:

Floor impact test from Day Design to Unit below.

Construction consisting of:

Tarkett Starfloor click ultimate luxury vinyl tiles, timber floorboards;

230 mm Concrete Slab


No Insulation

No Ceiling

Receiving room volume V: 46.00 m³

— Frequency range according to the
— curve of reference values (ISO 717-2)

Frequency f Hz	L'nT 1/3 Octave dB
50	45.1 B
63	50.3
80	47.5
100	48.3
125	57.7
160	57.7
200	56.4
250	54.9
315	55.6
400	55.4
500	56.6
630	58.2
800	55.0
1000	49.1
1250	44.2
1600	42.6
2000	40.8
2500	38.0
3150	37.3
4000	36.9
5000	30.5



B: L'nT =< value shown

Rating according to ISO 717-2

$$L'_{nT,w}(C_i) = 53 (-2) \text{ dB}$$

$$C_{i,50-2500} = -1 \text{ dB}$$

Evaluation based on field measurement results obtained in one-third-octave bands by an engineering method

No. of test report: 6577-1 A007

Name of test institute:

Date: 24/08/18

Signature: *Stephan Cank*

Standardized Impact Sound Pressure Level according to ISO 140-7

Field measurements of impact sound insulation of floors

Client: Tarkett Australia Pty Ltd

Date of test: 23/08/18

Description and identification of the building construction and test arrangement:

Floor impact test from Day Design to Unit below.

Construction consisting of:

Tarkett Starfloor click ultimate luxury vinyl tiles, timber floorboards

230 mm Concrete Slab


35 mm Glasswool Insulation (Density 11kg/m³)

13 mm plasterboard ceiling on 28 mm furring channel

Receiving room volume V: 46.00 m³

— Frequency range according to the curve of reference values (ISO 717-2)

Frequency f Hz	L'nT 1/3 Octave dB
50	48.2 B
63	52.2 B
80	45.1 B
100	51.9
125	56.8
160	55.6
200	53.4
250	52.6
315	52.4
400	51.9
500	54.0
630	52.4
800	50.3
1000	45.5
1250	40.9
1600	37.2
2000	35.4
2500	30.5
3150	27.4
4000	26.3
5000	21.1



B: L'nT =< value shown

Rating according to ISO 717-2

$$L'_{nT,w}(C_i) = 49 (0) \text{ dB}$$

$$C_{i,50-2500} = 0 \text{ dB}$$

Evaluation based on field measurement results obtained in one-third-octave bands by an engineering method

No. of test report: 6577-1 A003

Name of test institute:

Date: 24/08/18

Signature: *Stephan Lamb*

Standardized Impact Sound Pressure Level according to ISO 140-7

Field measurements of impact sound insulation of floors

Client: Tarkett Australia Pty Ltd

Date of test: 23/08/18

Description and identification of the building construction and test arrangement:

Floor impact test from Day Design to Unit below.

Construction consisting of:

Tarkett Starfloor click ultimate luxury vinyl tiles, timber floorboards;

230 mm Concrete Slab


35 mm Glasswool Insulation (Density 11kg/m³)

2 x 13 mm plasterboard ceiling on 28 mm furring channel

Receiving room volume V: 46.00 m³

— Frequency range according to the
— curve of reference values (ISO 717-2)

Frequency f Hz	L'nT 1/3 Octave dB
50	45.5 B
63	52.9 B
80	49.1 B
100	55.3
125	54.3
160	52.9
200	52.0
250	52.8
315	52.1
400	51.4
500	51.9
630	52.7
800	49.0
1000	43.1
1250	40.1
1600	35.5
2000	32.6
2500	27.8
3150	27.0
4000	24.9
5000	21.0



B: L'nT =< value shown

Rating according to ISO 717-2

$$L'_{nT,w}(C_i) = 49 (-1) \text{ dB}$$

$$C_{i,50-2500} = -1 \text{ dB}$$

Evaluation based on field measurement results obtained in one-third-octave bands by an engineering method

No. of test report: 6577-1 A006

Name of test institute:

Date: 24/08/18

Signature: *Stephan Lamb*