

LVT
HETEROGENEOUS

URBAN
NATURALS



Luxurious vinyl tiles for a naturally perfect effect.

Tarkett's range of Urban Natural luxury vinyl tiles recreates the warmth and beauty of timber and stone without the imperfections, colour variation or unevenness of tone of natural materials.

This creates a luxurious surface that will set your developments apart from the rest. All of this in just a fraction of the height of tiles or a natural or engineered timber floor, so you can maximise the interior space.

- Available in 1210mm x 190mm planks and 457mm x 457mm tiles
- Optimal interior air quality
- Warm and quiet underfoot
- TopClean polyurethane reinforced surface for easy cleaning
- 13 design options



Product Characteristics	Standards	Urban Naturals
PU treatment		PUR
Total thickness	EN 428	2.5mm
Wear layer thickness	EN 429	0.5mm
Total weight	EN 430	4000 g/m ²
Form of delivery	EN 426	Planks – 1210mm x 190mm Tiles – 457mm x 457mm
Warranty		10 years
Colours		13

Performance Characteristics	Standards	Urban Naturals
Reaction to fire	AS ISO 9239-1	Critical radiant flux 10.7 kW/m ² Smoke 59%.min
Slip resistance	AS 4586	Planks – R10 / P2 Tiles – R10 / P3

Recommended specification clauses for your project

Tarkett product numbers starting with 24822 and 24823.

1. Minimum 2.5mm gauge with minimum 0.5mm wear layer heterogeneous vinyl floor tile
2. Must meet Slip resistance R10 and P2 (Planks) or P3 (Tiles) as per AS 4586
3. 10 year commercial manufacturer's product warranty
4. Must be installed as per manufacturer's instructions and as per AS 1884
5. Contractor must confirm lead times with the manufacturer

**For information on our full range, contact us on 1300 851 484
or visit Tarkospec.com.au**

The information in this data sheet is correct at date of publication however, due to Tarkett's commitment for ongoing product improvement, we reserve the right to change this information without notice. Please note that Tarkett's instructions regarding installation, cleaning and maintenance must be observed. Please contact Tarkett for further information on these instructions.